



GTA 015

Adjusting dampers, 150 mm pitch

Product	GTA 015
Construction material	Aluminium
Finishing	Natural

GTA 015 dampers are used to accurately adjust and control the air flow and the air pressure in conditioning and ventilation systems and in air treatment plants. The dampers have natural aluminium finishing; U-shaped frame; extruded aluminium

wing-shaped opposite blades, operated from outside. The pins are made of galvanized steel (12 mm diameter) and are located in nylon bushes. The dampers have an aluminium side gasket that provide a quite good tightness

of the closed damper. A projecting pin control is used for manual or motor adjusting operations.

The GTA 010/T version offers higher tightness thanks to a PVC gasket on the blades.

Height (mm) H	200	300	400	500	600	700	800	900	1000	1100	1200	1300	1400	1500	1600	1700	1800	1900	2000
310	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
460	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
610	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
760	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
910	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
1060	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
1210	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
1360	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
1510	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
1660	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
1810	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
1960	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
2110	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
2260	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
2410	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•

Special types

- GTA 015 blades with PVC seal gasket
- GTA I 015 type with bearings outside the air flow
- GTA P 015 type with parallel blades

For duct mounted counter frame see technical sheet: WR 002
For wall mounted counter frame see technical sheet: WR 003
For manual controls and electric actuators see technical sheet: "Accessories for adjusting dampers"

Specify W x H in the order

Size

